



245 W. Roosevelt Road

Building 12, Suite 83

West Chicago, IL 60185

800-323-4498

AquaMark Domestic Booster Pump AM-LG1.5 240V Single Phase Specification

AQUAMARK MODEL AM-LG1.5, ENGINEERED PACKAGED PRESSURE BOOSTING SIMPLEX SYSTEM UTILIZING A VARIABLE FREQUENCY DRIVE. THE SYSTEM SHALL BE RATED FOR A FLOW OF 30 GPM WITH A 38 PSI INCREASE OVER INCOMING PRESSURE. SYSTEM INCLUDES STAINLESS STEEL LIQUID END PUMP WITH 1.5 HP, 3450 RPM, 3PHASE INVERTER DUTY ENERGY SAVING ODP MOTOR. THE SYSTEM WILL BE COMPLETELY PREFABRICATED INCLUDING ALL PIPING AND ELECTRICAL. ALL PLUMBING COMPONENTS FEATURE LOW-LEAD BRASS CONSTRUCTION. SYSTEM INCLUDES VARIABLE FREQUENCY DRIVE, NEMA-1 VFD CONTROL, TWO GLYCERIN FILLED PRESSURE GAUGES, GAUGE COCKS, BOILER DRAIN WITH CAP, 2.0 GALLON HYDROPNEUMATIC ACCUMULATOR TANK, 150 PSI RATED RELIEF VALVE AND LOW SUCTION PROTECTION SET TO 7PSI WITH AUTO-RESET. SYSTEM PROVIDED WITH 1 1/2" SUCTION SPRING LOADED CHECK VALVE AND SHALL UTILIZE 1 1/2" SUCTION AND DISCHARGE. SYSTEM INCLUDES A 6' GROUNDED WHIP PRE-WIRED TO THE VFD FOR EASY CONNECTION TO A WALL MOUNTED OUTLET PROVIDED BY ELECTRICIAN. START UP PHONE CONSULTATION WITH FACTORY TECHNICIAN AND A 24 MONTH FACTORY WARRANTY INCLUDED WITH PACKAGE.