Residential Pressure Booster Systems

AM-LG

AM-15V

• 1 HP

AM-LG 1.5

- 1 HP
- 3/4" Supply Line To 10 GPM
- 1" Supply Line To 15 GPM
- 1 1/4" Supply Line To 25 GPM
- 1.5 HP
- 1 1/2" Supply Line To 38 GPM

120 Volt, Comes With Attached 6' Cord & Plug 120 Volt, Comes With Attached 6' Cord & Plug 240 Volt Single Phase, Comes With Attached 6' Whip

AM-30V, AM-50V, AM-60V

AM-30V

AM-50V

AM-60V

- 2 HP
 - 40 PSI Boost @ 30 GPM
 - Up to 12 Shower Heads
 - Up to Five Story Building

 - Minimum 1.5" Supply Line
- 3 HP
- 36 PSI Boost @ 50 GPM
- Up to 20 Shower Heads
- Up to Seven Story Building
- Minimum 2" Supply Line
- 3 HP
- 45 PSI Boost @ 60 GPM
- Up to 24 Shower Heads
- Up to Nine Story Building
- Minimum 2" Supply Line

SPECIFICATIONS APPLY TO ALL THREE MODELS

208-240 Volt Single Phase or Three PhaseMeasures 24" W x 24" L x 24" H

AM-80V-1, AM-80V-3

AM-80V-1

AM-80V-3



- 33 PSI Boost @ 80 GPM
- Up to 32 Shower Heads
- Up to Six Story Building
- 240 Volt, 1 Phase
- Minimum 3" Supply Line
- 5 HP
- 40 PSI Boost @ 80 GPM
- Up to 32 Shower Heads
- Up to Nine Story Building
- 208 Volt, 3 Phase
- Minimum 3" Supply Line

SPECIFICATIONS APPLY TO BOTH MODELS

Measures 24" W x 30" L x 34" H





- 5 HP
- 50 PSI Boost @ 100 GPM
- Up to 40 Shower Heads
- Up to Ten Story Building
- 208 Volt Three Phase
- Requires Minimum 3" Supply Line
- Measures 24" W x 30" L x 34" H

AM-150\



- 7.5 HP
- 51 PSI Boost @ 150 GPM
- Up to 60 Shower Heads
- Up to Ten Story Building
- 208 Volt Three Phase
- Requires Minimum 3" Supply Line
- Measures 24" W x 30" L x 34" H

Manufactured by